

(MEDIUM DUTY)



DUAL PISTON CYLINDERS						PISTON AREA	
MODEL NO.	STROKE	A	B	C	D	EXT.	RET.
AC-F-G-1575-4*	1.00	6.62	3.56	3.50	6.75	15.81 SQ. IN.	7.51 SQ. IN.
AC-F-G-1575-6*	1.50	7.62	4.06				
AC-F-G-1575-8*	2.00	8.62	4.56				
AC-F-G-1575-12*	3.00	10.62	5.56				
AC-F-G-1575-16*	4.00	12.62	6.56				
AC-F-G-1575-20*	5.00	14.62	7.56				
AC-F-G-1575-24*	6.00	16.62	8.56				
AC-F-G-1840-4*	1.00	6.62	3.56	3.75	6.75	18.46 SQ. IN.	8.84 SQ. IN.
AC-F-G-1840-6*	1.50	7.62	4.06				
AC-F-G-1840-8*	2.00	8.62	4.56				
AC-F-G-1840-12*	3.00	10.62	5.56				
AC-F-G-1840-16*	4.00	12.62	6.56				
AC-F-G-1840-20*	5.00	14.62	7.56				
AC-F-G-1840-24*	6.00	16.62	8.56				
AC-F-G-2125-4*	1.00	6.62	3.56	4.00	7.25	21.30 SQ. IN.	10.26 SQ. IN.
AC-F-G-2125-6*	1.50	7.62	4.06				
AC-F-G-2125-8*	2.00	8.62	4.56				
AC-F-G-2125-12*	3.00	10.62	5.56				
AC-F-G-2125-16*	4.00	12.62	6.56				
AC-F-G-2125-20*	5.00	14.62	7.56				
AC-F-G-2125-24*	6.00	16.62	8.56				
AC-F-G-2430-4*	1.00	6.62	3.56	4.25	7.25	24.35 SQ. IN.	11.78 SQ. IN.
AC-F-G-2430-6*	1.50	7.62	4.06				
AC-F-G-2430-8*	2.00	8.62	4.56				
AC-F-G-2430-12*	3.00	10.62	5.56				
AC-F-G-2430-16*	4.00	12.62	6.56				
AC-F-G-2430-20*	5.00	14.62	7.56				
AC-F-G-2430-24*	6.00	16.62	8.56				

TRIPLE PISTON CYLINDERS						PISTON AREA	
MODEL NO.	STROKE	A	B	C	D	EXT.	RET.
AC-F-E3-2320-4*	1.00	9.12	3.56	3.50	6.75	22.99 SQ. IN.	7.51 SQ. IN.
AC-F-E3-2320-6*	1.50	10.62	4.06				
AC-F-E3-2320-8*	2.00	12.12	4.56				
AC-F-E3-2320-12*	3.00	15.12	5.56				
AC-F-E3-2320-16*	4.00	18.12	6.56				
AC-F-E3-2320-20*	5.00	21.12	7.56				
AC-F-E3-2320-24*	6.00	24.12	8.56				
AC-F-E3-2710-4*	1.00	9.12	3.56	3.75	6.75	26.97 SQ. IN.	8.84 SQ. IN.
AC-F-E3-2710-6*	1.50	10.62	4.06				
AC-F-E3-2710-8*	2.00	12.12	4.56				
AC-F-E3-2710-12*	3.00	15.12	5.56				
AC-F-E3-2710-16*	4.00	18.12	6.56				
AC-F-E3-2710-20*	5.00	21.12	7.56				
AC-F-E3-2710-24*	6.00	24.12	8.56				
AC-F-E3-3140-4*	1.00	9.12	3.56	4.00	7.25	31.24 SQ. IN.	10.26 SQ. IN.
AC-F-E3-3140-6*	1.50	10.62	4.06				
AC-F-E3-3140-8*	2.00	12.12	4.56				
AC-F-E3-3140-12*	3.00	15.12	5.56				
AC-F-E3-3140-16*	4.00	18.12	6.56				
AC-F-E3-3140-20*	5.00	21.12	7.56				
AC-F-E3-3140-24*	6.00	24.12	8.56				
AC-F-E3-3600-4*	1.00	9.12	3.56	4.25	7.25	35.81 SQ. IN.	11.78 SQ. IN.
AC-F-E3-3600-6*	1.50	10.62	4.06				
AC-F-E3-3600-8*	2.00	12.12	4.56				
AC-F-E3-3600-12*	3.00	15.12	5.56				
AC-F-E3-3600-16*	4.00	18.12	6.56				
AC-F-E3-3600-20*	5.00	21.12	7.56				
AC-F-E3-3600-24*	6.00	24.12	8.56				

ADDITIONAL STROKE LENGTHS ARE AVAILABLE IN .50" INCREMENTS

ALL PORTS 3/8-18 STANDARD PIPE TAP

Phone: (888) 654-9353

www.resistanceweldsupplies.com

PAGE 8